

Calculation of Confined Injection Zone Capacity

DJS Properties #2-14 Injection Zone

Calculation of Reservoir Volumes:					
POROSITY	0.23	FRACTION	FROM WELL LOG		
SW	0.80	FRACTION	WATER SATURATION - EVIDENCE OF GAS IN SWAB TESTING AND WATER ANALYSIS		
Sg	0.20	FRACTION	GAS SATURATION - EVIDENCE OF GAS IN ZONE FROM SWAB TESTING - RESIDUAL GAS		
GROSS VOLUME	94,700	ACRE-FT	FROM PLANNOMETRY CALCULATIONS BELOW		
NET/GROSS RATIO	0.90	FRACTION	FROM WELL LOGS		
PORE VOLUME	19,653	ACRE-FT			

Reservoir Isopach Area Planimeter Readings:					
CONTOUR LINE VALUE	AREA > (ACRES)	RATIO OF AREAS	CONTOUR (ft)	VOLUME (ACRE-FT)	
0	269.00				
100	234.00	0.8699	100	25,150.0	
200	205.00	0.8761	100	21,950.0	
300	173.00	0.8439	100	18,900.0	
400	144.00	0.8324	100	15,850.0	
500	113.00	0.7447	100	12,850.0	
TOTAL =>				94,700.0	ACRE-FT - GROSS BULK RESERVOIR VOLUME

Injection Zone Capacity:					
ITEM	VALUE	UNITS	COMMENTS - NOTES		
DATUM DEPTH:	5150	FT, BGL	AVERAGE DEPTH OF INJECTION ZONE		
AVERAGE TEMPERATURE:	251	DEG F	ML INVESTMENTS 1-3 PRODUCTION LOG		
INITIAL PRESSURE:	2276	PSI	8.6 PPG EQUIVALENT PORE PRESSURE AT DATUM DEPTH		
FRACURE PRESSURE:	3214	PSI	12 PPG EQUIVALENT PORE PRESSURE AT DATUM DEPTH		
MAXIMUM ALLOWABLE PRESSURE	2892	PSI	90% OF FRACTURE PRESSURE		
MAXIMUM PRESSURE INCREASE (dP)	61	PSI	MAXIMUM PORE PRESSURE LESS INITIAL PRESSURE		
AVERAGE PRESSURE	2584	PSI	AVERAGE OF INITIAL PRESSURE AND MAXIMUM ALLOWABLE PRESSURE		
WATER SATURATION	75%	PPM CI	ESTIMATED AVERAGE		
WATER COMPRESSIBILITY	3.48E-06	1/PSI	OCAF'S CORRELATION		
GAS COMPRESSIBILITY	3.87E-04	1/PSI	MEEHAN ET AL., GAS GRAVITY = 0.65 FROM ML INVESTMENTS 1-10 WELL		
ROCK PORE SPACES COMPRESSIBILITY	3.55E-06	1/PSI	HALL'S CORRELATION		
RESERVOIR WATER VOLUME INITIAL	15,850.0	ACRE-FT	SW * VOLUME * SW		
RESERVOIR WATER VOLUME INITIAL	121,653,439	RBBLs	PORE VOLUME * SW		
RESERVOIR WATER VOLUME COMPRESSION	261,022	RBBLs	dP * WATER COMPRESSIBILITY * INITIAL WATER VOLUME		
RESERVOIR GAS SPACE VOLUME INITIAL	3,921	ACRE-FT	PORE VOLUME * SG		
RESERVOIR GAS SPACE VOLUME INITIAL	30,415,860	RBBLs	PORE VOLUME * SG		
Gas Space Volume Compression	7,250,191	RBBLs	dP * WATER COMPRESSIBILITY * INITIAL GAS VOLUME		
Pore Space Volume Increase	268,141	ACRE-FT	dP * PORE SPACE COMPRESSIBILITY		
Total Pore Space Volume Increase	7,773,484	RBBLs	SUM OF WATER, GAS, AND PORE SPACE COMPRESSION		
Bw (water formation volume factor):	1.055	RBBL/STBb	MCCAIN'S CORRELATION		
Total Stock Tank Barrels Capacity	7,368,241	STBBLs	ADJUST TO SURFACE CONDITIONS BY DIVIDING BY WATER FORMATION VOLUME FACTOR (Bw)		

Formation Water Factor:

McCain Correlation
Datum Temperature: 251 deg F
Datum Pressure: 2276 psi
dV/dP: 0.05814
dV/dT: -0.00333






Figure 2.22 Hall's correlation of porosity and c_p .



http://petrowiki.org/Produced_water_formating_volume_factor

$$\begin{aligned} \frac{dP}{dP_f} &= \left(1 + \frac{\partial P}{\partial T} \right) \left(1 + \frac{\partial P}{\partial Sg} \right), \quad (1) \\ \text{where } \Delta P_{dP_f} &= -1.0000 \times 10^{-3} + 1.31391 \times 10^{-4} T + 5.50054 \times 10^{-7} T^2, \quad (2) \\ \text{and } \Delta P_{dP_g} &= 1.95301 \times 10^{-4} P^2 - 1.72834 \times 10^{-5} P^3, \\ &-3.00022 \times 10^{-6} P^4 - 2.23346 \times 10^{-10} P^5, \quad (4) \end{aligned}$$


where P = pressure in psia, and T = temperature in °F. McCain reported that this correlation agrees with a limited set of published experimental data to within 2%. The correlation is valid for temperatures between 60°F and 250°F, and pressures to 5,000 psia. An increase in dissolved salinity causes a slight increase in ΔP_{dP_f} , which offset each other to within 1%.



Aquifer Production for Drinking Water Scenario			
Item	Value	Units	Comments - notes
Datum Depth:	5,150	ft. BGL	average depth of injection zone
Average Temperature	251	deg F	ML Investments 1-3 production log
Initial Pressure:	2276	psi	8.6 ppg equivalent pore pressure at datum depth
Gas Gravity:	0.6513	kg/m³	
Nitrogen content:	0.5273	mol%	
CO2 content:	0.1413	mol%	
H2S content:	0	mol%	
Supercompressibility Factor => Zi	#NAME? NA		
Gas Formation Volume Factor => Bg	#NAME? SCF:RCF		
Initial Reservoir Pore Volume	19,603	acre-ft	
Initial Gas Saturation	0.88	fraction	
Initial Water Saturation	0.88	fraction	
Original Gas In Place	3500.00	acre-ft	
Original Water In Place			

$$G = 43560 \cdot A \cdot h \cdot Sg \cdot Prz \cdot Psc$$

Calculation of Confined Injection Zone Capacity																																																																																											
D/S Properties #2-14 Injection Zone																																																																																											
Calculation of Reservoir Volumes:																																																																																											
<table border="1"> <tr> <td>Porosity</td><td>0.23</td><td>fraction</td><td></td></tr> <tr> <td>Sw</td><td>0.80</td><td>fraction</td><td>water saturation - evidence of gas in swab testing and water analysis</td></tr> <tr> <td>Sg</td><td>0.20</td><td>fraction</td><td>gas saturation - evidence of gas in zone from swab testing - residual gas</td></tr> <tr> <td>Gross Volume</td><td>94,700</td><td>acre-ft</td><td>from planimetry calculations below</td></tr> <tr> <td>Net/Gross Ratio</td><td>0.88</td><td>fraction</td><td>from well logs</td></tr> <tr> <td>Pore Volume</td><td>19,603</td><td>acre-ft</td><td></td></tr> </table>				Porosity	0.23	fraction		Sw	0.80	fraction	water saturation - evidence of gas in swab testing and water analysis	Sg	0.20	fraction	gas saturation - evidence of gas in zone from swab testing - residual gas	Gross Volume	94,700	acre-ft	from planimetry calculations below	Net/Gross Ratio	0.88	fraction	from well logs	Pore Volume	19,603	acre-ft																																																																	
Porosity	0.23	fraction																																																																																									
Sw	0.80	fraction	water saturation - evidence of gas in swab testing and water analysis																																																																																								
Sg	0.20	fraction	gas saturation - evidence of gas in zone from swab testing - residual gas																																																																																								
Gross Volume	94,700	acre-ft	from planimetry calculations below																																																																																								
Net/Gross Ratio	0.88	fraction	from well logs																																																																																								
Pore Volume	19,603	acre-ft																																																																																									
Reservoir Isopach Area Planimeter Readings:																																																																																											
<table border="1"> <thead> <tr> <th>CONTOUR LINE VALUE</th><th>AREA > (acres)</th><th>RATIO OF AREAS</th><th>CONTOUR (ft.)</th><th>DELTAL VOLUME (acre-ft)</th></tr> </thead> <tbody> <tr><td>0</td><td>269.00</td><td></td><td></td><td></td></tr> <tr><td>100</td><td>234.00</td><td>0.8695</td><td>100</td><td>25,150.0</td></tr> <tr><td>200</td><td>205.00</td><td>0.8761</td><td>100</td><td>21,950.0</td></tr> <tr><td>300</td><td>173.00</td><td>0.8827</td><td>100</td><td>18,850.0</td></tr> <tr><td>400</td><td>144.00</td><td>0.8834</td><td>100</td><td>15,850.0</td></tr> <tr><td>500</td><td>113.00</td><td>0.7847</td><td>100</td><td>12,850.0</td></tr> </tbody> </table>				CONTOUR LINE VALUE	AREA > (acres)	RATIO OF AREAS	CONTOUR (ft.)	DELTAL VOLUME (acre-ft)	0	269.00				100	234.00	0.8695	100	25,150.0	200	205.00	0.8761	100	21,950.0	300	173.00	0.8827	100	18,850.0	400	144.00	0.8834	100	15,850.0	500	113.00	0.7847	100	12,850.0																																																					
CONTOUR LINE VALUE	AREA > (acres)	RATIO OF AREAS	CONTOUR (ft.)	DELTAL VOLUME (acre-ft)																																																																																							
0	269.00																																																																																										
100	234.00	0.8695	100	25,150.0																																																																																							
200	205.00	0.8761	100	21,950.0																																																																																							
300	173.00	0.8827	100	18,850.0																																																																																							
400	144.00	0.8834	100	15,850.0																																																																																							
500	113.00	0.7847	100	12,850.0																																																																																							
TOTAL => 94,700.0 acre-ft = gross bulk reservoir volume																																																																																											
Injection Zone Capacity																																																																																											
<table border="1"> <tr> <td>Item</td><td>Value</td><td>Units</td><td>Comments - notes</td></tr> <tr> <td>Datum Depth:</td><td>5150</td><td>ft. BGL</td><td>average depth of injection zone</td></tr> <tr> <td>Average Temperature</td><td>251</td><td>deg F</td><td>ML Investments 1-3 production log</td></tr> <tr> <td>Initial Pressure:</td><td>2276</td><td>psi</td><td>8.6 ppg equivalent pore pressure at datum depth</td></tr> <tr> <td>Fracture Pressure:</td><td>3214</td><td>psi</td><td>12 ppg equivalent pore pressure at datum depth</td></tr> <tr> <td>Maximum Allowable Pressure</td><td>2892</td><td>psi</td><td>90% of fracture pressure</td></tr> <tr> <td>Maximum Pressure Increase (dP)</td><td>616</td><td>psi</td><td>maximum allowable pressure less initial pressure</td></tr> <tr> <td>Assume dP</td><td>560</td><td>psi</td><td>average of initial pressure and maximum allowable pressure</td></tr> <tr> <td>Water Salinity</td><td>750</td><td>ppm O</td><td>estimated average</td></tr> <tr> <td>Water Compressibility</td><td>3.48E-06</td><td>1/psi</td><td>Ost's Correlation</td></tr> <tr> <td>Bar Compensability</td><td>0.0000</td><td>1/psi</td><td>McCaill's Correlation</td></tr> <tr> <td>Rock pore volume compressibility</td><td>3.92E-06</td><td>1/psi</td><td>Hall's Correlation</td></tr> <tr> <td>Reservoir Water Volume Initial</td><td>15,682</td><td>acre-ft</td><td>Pore Volume = Sw</td></tr> <tr> <td>Reservoir Water Volume Final</td><td>121,663,439</td><td>RBbls</td><td>dp * gas compressibility * initial water volume</td></tr> <tr> <td>Reservoir Water Volume Compression</td><td>3.921</td><td>acre-ft</td><td>Pore Volume = Sw</td></tr> <tr> <td>Reservoir Gas Space Volume Initial</td><td>30,415,860</td><td>RBbls</td><td>Pore Volume = Sg</td></tr> <tr> <td>Reservoir Gas Space Volume Final</td><td>7,250,191</td><td>RBbls</td><td>dp * gas compressibility * initial gas volume</td></tr> <tr> <td>Gas Pore Space Compressibility</td><td>0.0000</td><td>1/psi</td><td>dp * gas compressibility * pore space compressibility</td></tr> <tr> <td>Gas Pore Space Increase</td><td>0.0000</td><td>1/psi</td><td>dp * gas compressibility * initial gas volume</td></tr> <tr> <td>Total Pore volume increase</td><td>7,773,494</td><td>RBbls</td><td>sum of water, gas, and pore space compression</td></tr> <tr> <td>Bw (water formation volume factor):</td><td>1.055</td><td>RBbl/STBb</td><td>McCain's Correlation</td></tr> <tr> <td>Total Stock Tank Barrels Capacity</td><td>7,388,241</td><td>STBbs</td><td>adjust to surface conditions by dividing by water formation volume factor (Bw)</td></tr> </table>				Item	Value	Units	Comments - notes	Datum Depth:	5150	ft. BGL	average depth of injection zone	Average Temperature	251	deg F	ML Investments 1-3 production log	Initial Pressure:	2276	psi	8.6 ppg equivalent pore pressure at datum depth	Fracture Pressure:	3214	psi	12 ppg equivalent pore pressure at datum depth	Maximum Allowable Pressure	2892	psi	90% of fracture pressure	Maximum Pressure Increase (dP)	616	psi	maximum allowable pressure less initial pressure	Assume dP	560	psi	average of initial pressure and maximum allowable pressure	Water Salinity	750	ppm O	estimated average	Water Compressibility	3.48E-06	1/psi	Ost's Correlation	Bar Compensability	0.0000	1/psi	McCaill's Correlation	Rock pore volume compressibility	3.92E-06	1/psi	Hall's Correlation	Reservoir Water Volume Initial	15,682	acre-ft	Pore Volume = Sw	Reservoir Water Volume Final	121,663,439	RBbls	dp * gas compressibility * initial water volume	Reservoir Water Volume Compression	3.921	acre-ft	Pore Volume = Sw	Reservoir Gas Space Volume Initial	30,415,860	RBbls	Pore Volume = Sg	Reservoir Gas Space Volume Final	7,250,191	RBbls	dp * gas compressibility * initial gas volume	Gas Pore Space Compressibility	0.0000	1/psi	dp * gas compressibility * pore space compressibility	Gas Pore Space Increase	0.0000	1/psi	dp * gas compressibility * initial gas volume	Total Pore volume increase	7,773,494	RBbls	sum of water, gas, and pore space compression	Bw (water formation volume factor):	1.055	RBbl/STBb	McCain's Correlation	Total Stock Tank Barrels Capacity	7,388,241	STBbs	adjust to surface conditions by dividing by water formation volume factor (Bw)
Item	Value	Units	Comments - notes																																																																																								
Datum Depth:	5150	ft. BGL	average depth of injection zone																																																																																								
Average Temperature	251	deg F	ML Investments 1-3 production log																																																																																								
Initial Pressure:	2276	psi	8.6 ppg equivalent pore pressure at datum depth																																																																																								
Fracture Pressure:	3214	psi	12 ppg equivalent pore pressure at datum depth																																																																																								
Maximum Allowable Pressure	2892	psi	90% of fracture pressure																																																																																								
Maximum Pressure Increase (dP)	616	psi	maximum allowable pressure less initial pressure																																																																																								
Assume dP	560	psi	average of initial pressure and maximum allowable pressure																																																																																								
Water Salinity	750	ppm O	estimated average																																																																																								
Water Compressibility	3.48E-06	1/psi	Ost's Correlation																																																																																								
Bar Compensability	0.0000	1/psi	McCaill's Correlation																																																																																								
Rock pore volume compressibility	3.92E-06	1/psi	Hall's Correlation																																																																																								
Reservoir Water Volume Initial	15,682	acre-ft	Pore Volume = Sw																																																																																								
Reservoir Water Volume Final	121,663,439	RBbls	dp * gas compressibility * initial water volume																																																																																								
Reservoir Water Volume Compression	3.921	acre-ft	Pore Volume = Sw																																																																																								
Reservoir Gas Space Volume Initial	30,415,860	RBbls	Pore Volume = Sg																																																																																								
Reservoir Gas Space Volume Final	7,250,191	RBbls	dp * gas compressibility * initial gas volume																																																																																								
Gas Pore Space Compressibility	0.0000	1/psi	dp * gas compressibility * pore space compressibility																																																																																								
Gas Pore Space Increase	0.0000	1/psi	dp * gas compressibility * initial gas volume																																																																																								
Total Pore volume increase	7,773,494	RBbls	sum of water, gas, and pore space compression																																																																																								
Bw (water formation volume factor):	1.055	RBbl/STBb	McCain's Correlation																																																																																								
Total Stock Tank Barrels Capacity	7,388,241	STBbs	adjust to surface conditions by dividing by water formation volume factor (Bw)																																																																																								



http://petrowiki.org/Produced_water_formation_volume_factor


$$\begin{aligned} K_w &= (1 + \Delta \sigma_w)(1 + \Delta \sigma_g) \dots \\ \text{where} \\ \Delta \sigma_{wp} &= 1.0000 \times 10^{-2} \cdot t - 1.7384 \times 10^{-3} t^2 \dots \\ -0.38812 \times 10^{-3} t^2 + 2.2348 \times 10^{-4} t^3 \dots \end{aligned}$$

Notes: t is pressure in psia, and $\Delta \sigma_w$ is the change in water formation volume factor. This correlation applies only to a limited number of field cases. An increase in pressure will cause a slight increase in K_w , and a decrease in pressure will cause a slight decrease in K_w .

1 GAS COEFFICIENT OF ISOTHERMAL COMPRESSIBILITY				
VERSION 1.1 (1979)				
GAS GRAVITY = 0.6513				
COND. OR MISC. (C/M) = 0.5272				
PERCENT CO2 = 0.1413				
PERCENT H2S = 0				
CALCULATE				
A B C D E				
11 PRESSURE 70 100 150 250				
12 1,02E-02 3,49E-03 3,44E-03 3,40E-03				
13 300 3,52E-03 3,49E-03 3,44E-03 3,40E-03				
14 400 3,53E-03 3,49E-03 3,44E-03 3,40E-03				
15 700 1,62E-03 1,58E-03 1,53E-03 1,48E-03				
16 1,000 1,09E-03 1,05E-03 1,01E-03 9,69E-04				
17 1,100 1,09E-03 1,05E-03 9,99E-04 9,49E-04				
18 1,200 9,04E-04 7,71E-04 7,38E-04 6,93E-04				
19 1,500 5,88E-04 5,60E-04 5,42E-04 5,17E-04				
20 1,900 4,98E-04 4,63E-04 4,36E-04 4,07E-04				
21 2,100 3,91E-04 3,47E-04 3,21E-04 2,94E-04				
22 2,300 3,61E-04 3,79E-04 3,89E-04 3,87E-04				
23 2,500 3,40E-04 3,44E-04 3,44E-04 3,44E-04				
24 2,844 3,40E-04 3,44E-04 3,44E-04 3,44E-04				





Structure Map (below Ground level datum of 2300' ASL): Top Sand 3
 Proposed Injection Zone - Scale 1": 600'



DMS 9/2017

Isopach Map of Sands 3,4,5 –showing Faulting
 100' Contour Interval – Scale 1":600'





[Reply](#) [Reply All](#) [Forward](#) [IM](#)
 Wed 9/20/2017 12:07 PM

David M. Smith

RE: Geologic support for proposed injection well DJS #2-14

To Dale R. Hayes; Mofazzal Bhuiyan; Michael Christian
 Cc Mike H. McMennamy

[Conversation Filer](#) [TeamViewer](#) [+ Get more add...](#)

I can have Karl Planimeter a hard copy to calculate gross volumes using different methods.

Areas are:


0' contour – 269 acres
 100' – 234 ac.
 200' – 205 ac.
 300' – 173 ac.
 400' – 144 ac.
 500' – 113 ac.

The volume should be the same as 500' x 188 acres = 94,000 ac. ft.

Regards,
Dave

1 Input Data	Swc	0.3	Lithology		A Modified Method for Predicting Relative Permeability	
	Sgc	0.3				
	Krw @ Sgc	0.8	Sandstone			
	Krg @ Swc	1				
2 Numerical Regression	T-Factor	Sw	Krw	Krg	BY: Mohamed Ameen, Mahmoud Tantawy and Ahmed Gawish	
	0.63	0.455	0.236	0.670		
	Before Adjusting	nw	ng	Adjusting Factors		
		1.29	0.82			
3 Predicted Relative Permeability data	After Adjusting	nw	ng	A	B	$F_w = 1 / [1 + (Krg * \mu_{go}) / (Krw * \mu_w)]$
		4.82	1.98	3.74	2.43	
	No	Sw	Krw	Krg		
	1	0.3000	0.0000	1.0000		
	2	0.3400	0.0000	0.8114		
	3	0.3800	0.0003	0.6423		
	4	0.4200	0.0024	0.4928		
	5	0.4600	0.0096	0.3629		
	6	0.5000	0.0282	0.2528		
	7	0.5400	0.0681	0.1623		
	8	0.5800	0.1432	0.0917		
	9	0.6200	0.2726	0.0410		
	10	0.7000	0.8000	0.0000		

BY: Mohamed Ameen, Mahmoud Tantawy and Ahmed
Gawish



Fw

Fault Slip Potential:	47.5 mm =	3000 feet	Scale:	X mm	Y mm	X km	Y km	m m	x ft/m	x in/ft	x cm/in	/ cm	/ m	dy ft	dx in	dy/dx 1	Radians 1	Degrees 0.785398 45
Well Location:	41.5	33.5				0.798897	0.644893											
								33.5	63.15789	12	2.54	100	1000					
									2115.789	25389.47	64489.26	64489.26	0.644893					
Beginning	End	Beginning	End	dy	dx	dy/dx	Radians	Degrees	Mid Point of Fault	Length of Fault								
X mm	Y mm	X mm	Y mm	X	Y	X	X	Y										
Fault 1	8	47.9	46.75	22.9	0.154004	0.9221	0.899962	0.440837	-0.48126	0.745958	-0.64516	-0.57297	-32.8285	122.8285	0.526983	0.681469	0.887732	
Fault 2	46.75	22.9	108.5	7.5	0.899962	0.440837	2.088682	0.144379	-0.29646	1.18872	-0.24939	-0.24441	-14.0035	104.0035	1.494322	0.292608	1.22513	
Fault 3	108.75	7.5	82.25	49.25	2.093495	0.144379	1.583356	0.948088	0.803709	-0.51014	-1.57547	-1.00523	-57.5955	147.5955	1.838425	0.546234	0.95194	
Fault 4	82.25	49.25	8	47.9	1.583356	0.948088	0.154004	0.9221	-0.02599	-1.42935	0.01818	0.01818	1.041627	88.95837	0.86868	0.935094	1.429588	

